



Main

Range of product	Zelio Relay
Product or component type	Solid state relay
Device short name	SSM
Number of channels	2
Network number of phases	2 phases


Complementary

Mounting support	Symmetrical DIN rail
[In] rated current	6 A
Output voltage	48...600 V AC
Control circuit voltage	4...32 V DC
Contacts type and composition	2 NO
Tightening torque	0.5...0.8 N.m for output 0.5...0.8 N.m for input
Connections - terminals	Screw terminals 1 x 0.3...1 x 2.5 mm ² for output - AWG 22...AWG 14 Screw terminals 1 x 0.3...1 x 1.5 mm ² for input - AWG 22...AWG 16
Capacitance unbalance	<= 10 pF for input/output
Insulation resistance	1000 MOhm at 500 V DC
Local signalling	LED green for input status
Switching voltage	<= 1 V DC turn-off >= 4 V DC turn-on
Input current limits	14...16.87 mA
Solid state output type	SCR output Random voltage switching
Load current	0.15...6 A
Absolute maximum voltage	1200 V
Surge current	<= 750 A for 20 ms <= 715 A for 16.6 ms
Voltage drop	1.3 V on-state
Motor power hp	0.16 hp at 40 °C 240 V AC
Maximum I ² t for fusing	2330 A ² .s for 8.33 ms at 60 Hz half cycle 2560 A ² .s for 10 ms at 50 Hz half cycle
Leakage current	<= 0.25 mA off-state
DV/Dt	500 V/μs off-state at maximum voltage
Response time	0.1 ms turn-on 0.5 cycle turn-off
Cos phi	>= 0.5 with maximum load
Overvoltage category	III
Width	18 mm
Height	90.3 mm
Depth	84.4 mm
Product weight	0.09 kg


Environment

Flame retardance	V0 conforming to UL 94
Dielectric strength	2.5 kV AC for input or output to case 2.5 kV AC for input/output
Pollution degree	2
Standards	IEC 61000 IEC 60950-1 IEC 62314
Product certifications	CSA RoHS UL REACH
Marking	CE
IP degree of protection	IP20
Ambient air temperature for operation	-30...80 °C
Ambient air temperature for storage	-30...100 °C

Dimensions



Derating Curves



A : Load Current (Amperes)

B : Ambient Temperature (°C)

1 : Multiple units, no minimum spacing between components

2 : Installed single unit, distance to adjacent components more than 18 mm