


SPECIFICATIONS					
CONTACT CARRIER MATERIAL	NYLON OR TPU				
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK				
CONTACT MATERIAL/PLATING	BRASS/GOLD				
HOUSING/LOCKNUT MATERIAL/PLATING	BRASS/NICKEL				
RATED CURRENT [A]	4.0 A				
RATED VOLTAGE [V]	250 V				
OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLUE				
CONDUCTOR INSULATION MATERIAL	PVC w/NYLON OVERCOAT				
NUMBER OF CONDUCTORS [AWG]	4x18 AWG				
DRAIN/SHIELD	20 AWG DRAIN/ALUMINIZED POLYESTER FOIL SHIELD				
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)				
PROTECTION CLASS	NEMA 1,3,4,6P AND IEC IP68, IP69K				
CABLE RATING	UL: ITC-ER, DIRECT BURIAL/PLTC-ER/AWM, 105C, 300V				
	CSA: CMX-OUTDOOR-CMG/AWM, 105C, 300V				



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

## NOTES:

- 1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- 2. STRIP AND TIN LENGTHS ARE FOR REFERENCE ONLY; SOME LENGTHS MAY NOT BE STRIPPED AND TINNED.

С	DRAWING PROCESSED AS PART OF ECO 33971	СВМ	04/07/11	33971
REV	DESCRIPTION	BY	DATE	ECO NO.

## SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS  1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 554- 1-800-544-7769 (763) 553-7300 (763) 553-0708 fturck.com			
MATERIAL		DRFT RDS	DATE 01/11/10	DESCRIPTION DESCRIPTION	707 *	
SEE SPECIFICATIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DSGN	SCALE 1=1.0	P-RKG 5.34T-1	-   / 2 / - *	
		UNIT OF MEASUREMENT		IDENTIFICATION NO.		REV
FINISH SEE SPECIFICATIONS	CONTACT TURCK FOR MORE INFORMATION	MILLIMETE	ER [ INCH ]	IDENTIFICATION NO.		C
1	DO NOT SCALE	THIS DRAWING	FILE: 777025746	SHEET	1 OF 1	