


HIGH TEMPERATURE USB DATA LOGGER

316 SS Construction, Up To 32,510 Readings



The **MODEL DW-USB-1-HT** High Temperature USB Data Logger allows users to monitor temperatures up to 257°F (125°C). The rigid, stainless steel enclosure protects the sensor against corrosion, impact, and water ingress.

FEATURES/BENEFITS

- Easy to use configuration software
- Integral USB plug
- 316 SS housing

APPLICATIONS

- Thermal testing
- Process monitoring or troubleshooting

MODEL CHART

Model	Description
DW-USB-1-HT	High temperature USB data logger

SPECIFICATIONS

Range: -40 to 257°F (-40 to 125°C).

Accuracy: ±1°F (±0.5°C).

Resolution: 0.2°F (0.1°C).

Memory Size: 32,510 readings.

Sampling Mode: Continuous or stop on memory full.

Sampling Rate: Selectable from 1 s. to 12 hours.

Computer Requirements: Windows® 2000, Windows® XP, Windows Vista®, and Windows® 7; 32 or 64-bit operating systems.

Power Requirements: 3.6 V 2/3 AA lithium metal battery, included, user replaceable.

Battery Life: Approximately 1 to 3 years.

Housing: 316 SS.

Enclosure Rating: IP67/NEMA 4X.

Alarms: Programmable high/low.

Interface: USB port.

Weight: 4.6 oz (130.4 g).

Agency Approvals: CE.

Windows® and Windows Vista® are registered trademarks of Microsoft Corporation.