

G UPDATE RATED VOLTAGE

REV DESCRIPTION

CDEOLE	TICATIONIC			
SPECIFICATIONS				
CONTACT CARRIER MATERIAL	TPU			
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW			
CONTACT MATERIAL/PLATING	BRASS/GOLD			
COUPLING NUT MATERIAL/FINISH	NYLON/BLACK			
RATED CURRENT [A]	8.0 A			
RATED VOLTAGE [V]	600 V			
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW			
CONDUCTOR INSULATION MATERIAL	PVC			
NUMBER OF CONDUCTORS [AWG]	6x18 AWG			
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)			
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67			

-	* METERS SEE NOTES 1	-
7/8-16UN #26.0 [1.02]	Ø8.4 [0.33]	50.0 [1.97]

OADI E LENOTI L	TOLEDANOE *			
CABLE LENGTH	TOLERANCE *			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE *			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			
* UNLESS OT	THERWISE SPECIFIED			

## SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:	
1. "*" INDICATES CABLE LENGTH IN METERS. LENGTHS.	CONTACT TURCK TO ORDER SPECIFIC

J			RELATED DOCUMENTS  1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	Sensors and Automatic	MINNEAPC 1-800 (763) (763)	CAMPUS DRIVE DLIS, MN 5544* D-544-7769 553-7300 553-0708 fa Irck.com	
TO ORDER SPECIFIC		MATERIAL  SEE SPECIFICATIONS		DRFT CBM	DATE 01/08/01	DESCRIPTION RK 61-*M				
				ALL DIMENSIONS DISPLAYED ON THIS	APVD	SCALE 1=1.0		IX OI - IVI	— · · [V]	
				DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME	MEASUREMENT DENTIFICATION NO				
			FINISH	7	AM LINETED [INCL]		IDENTIFICATION NO.		REV	
				CONTACT TURCK FOR MORE		MILLIMETER [ INCH ]			l G	
	RDS	03/19/14	45225	SEE SPECIFICATIONS	INFORMATION					
	BY	DATE	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: 777000160		SHEET 1 OF